

# COA-2016-F

## Electronic CO<sub>2</sub> Analyzer

New electronic CO<sub>2</sub> analyzer specifically designed to monitor CO<sub>2</sub>, O<sub>2</sub> and temperature for the verification of incubators in research, IVF, and pharmaceutical markets. This unit has been developed to incorporate the latest technology and specification requirements, that provide the user with a fast, simple to use and accurate piece of laboratory kit.

### Benefits

- Improved accuracy on CO<sub>2</sub> and O<sub>2</sub> readings
- Quick verification of CO<sub>2</sub> and O<sub>2</sub> incubator levels
- Time saving with dual temperature probes
- Large data storage and user friendly software and download
- Easy to read large well lit display
- Built in gas moisture removal

### Applications

- Calibration of inbuilt CO<sub>2</sub> sensor in Esco CelCulture® CO<sub>2</sub> incubators
- Calibration of inbuilt temperature sensor in Esco CelCulture® CO<sub>2</sub> incubators
- Measurement of CO<sub>2</sub> and O<sub>2</sub> levels in CO<sub>2</sub> incubators
- Measurement of temperature in CO<sub>2</sub> incubators



## Product Specification

### COA-2016-F (Electronic CO<sub>2</sub> Analyzer)

#### Gas Ranges

Gas Measured	CO <sub>2</sub>	By custom dual wavelength infra-red cell reference channel
	O <sub>2</sub>	By internal electrochemical cell
Range	CO <sub>2</sub>	0-20%
	O <sub>2</sub>	0-100%
Measurement Accuracy	Gas	CO <sub>2</sub> / O <sub>2</sub>
	CO <sub>2</sub>	Accuracy ± (1% range +2% of reading) at reference conditions Temperature dependence ± 0.2% reading °C (typical at 5% CO <sub>2</sub> ) Pressure dependence ± 0.02% of reading/hPa (typical at 5% CO <sub>2</sub> )
	O <sub>2</sub>	±1.0% Full scale at constant temperature and pressure ±2.0% Full scale over operating temperature range
Response Time T <sup>90</sup>	CO <sub>2</sub>	≤20 seconds
		≤60 seconds

#### Facilities

Temperature (Optional)	x2 using optional probes, range 0°C to +50°C
Temperature Accuracy, Typical	± 0.2°C from 32 to 44°C, ± 0.5°C over the rest of range
Barometric Pressure	800-1200 mbar
Visual and Audible Alarm	Selectable CO <sub>2</sub> and O <sub>2</sub> alarm levels
Communications	USB type B mini-connector, HID device class
Data Storage	1000 reading sets +270 events

### Environmental Conditions

Operating Temperature Range	5°C - 40°C
Barometric Pressure	± 500 mbar from calibration pressure
IP Rating	IP40

### Power Supply

Battery Type	Li Ion
Battery Life	10 hours (8 hours with pump)
Battery Lifetime	>300 Cycles
Battery Charger	5 V DC external power supply and internal charging circuit
Charge Time	3 hours
Alternative Power	USB connector DC power supply

### Pump

Flow	100 cc/min typically
------	----------------------

### Environmental Conditions

Operating Temperature Range	5°C - 40°C
Barometric Pressure	± 500 mbar from calibration pressure

### Physical

Case Material	ABS / Polypropylene with silicone rubber inserts
Keys	17 Resin-capped silicone rubber keys
Display	Liquid crystal display, 128 x 64 pixel with RGB LED backlight
Gas Sample Filters	Built-in gas dryer tube to remove moisture Replaceable PTFE water trap filter
Weight	495 g
Dimension (W x D x H)	165 x 100 x 55 mm (6.5" x 3.9" x 2.2")



21 Changi South Street 1, Singapore 486 777  
 Tel: +65 6542 0833 • Fax: +65 6542 6920  
 email: [medical@escoglobal.com](mailto:medical@escoglobal.com) • website: [www.medical.escoglobal.com](http://www.medical.escoglobal.com)



9010295 Gas Analyzer Brochure\_A4\_062016  
 All trademarks and logos in this material are the property of  
 ESCO Medical and the respective companies.